

WRD-P6 / SYNTHETIC CARRIER POLYMER LINE

# Spider Line P6 Series

## Ultra-Thin Precision Luxury Extraction Line

Engineered specifically for late-model European luxury sedans and high-end imports. The P6 features an ultra-thin 0.65 mm solid braid construction with 279 lbs of breaking strength, designed to slice effortlessly through zero-tolerance panel gaps where thicker standard lines would bind or tear delicate trims.



<b>279 lbs</b> BREAKING STRENGTH	<b>0.65 mm</b> DIAMETER PROFILE	<b>Ultra-thin precision</b> BRAID GEOMETRY
-------------------------------------	------------------------------------	---

### Ultra-thin precision profile

Dimensioned at just 0.65 mm to slide through the tightest zero-tolerance panel interfaces without binding.

### Maximum salvage safety

Designed to safely slice close-matted urethane tracks, fully preserving expensive decorative trim and moldings.

### Low mechanical resistance

Razor-thin footprint slices cleanly with minimal drag, reducing manual hand crank or drill torque strain.

### Precision duty lifespan

Built for high-end precision, yielding up to 4 complete extraction runs per segment when handled with care.

### TECHNICAL SPECIFICATIONS

Diameter range	0.65 mm
Breaking strength	279 lbs
Braid geometry	Solid braid construction
Standard spool size	96 meters (315 ft)
Length markings	Unmarked continuous line
Reusability rating	Up to 4 cuts
Salvage rating	Great (the absolute best option for mold/clip preservation)

### COMPATIBLE SYSTEMS

Spider 3 / 3M (WRD-S3 / S3M)	Spider 4 / 4M (WRD-S4 / S4M)
Orange Bat (WRD-OB)	Bison (WRD-BN)

### FIELD OPERATION NOTES

- **Late-model imports;** Strictly recommended for late-model European luxury imports (e.g., Mercedes, BMW, Audi) where glass-to-body clearance is minimal.
- **Warranty warning;** Deploying steel wire in WRD spool housings will result in premature wear, scoring of guides, and will void warranties.
- **Tension control;** Due to its 0.65 mm thinness, this line is subject to fatigue. Do not power through snags; back off torque and clear snags manually.

### CUT PRO PERFORMANCE LINE SELECTION GUIDE

LINE SERIES	SKU	PROFILE & BRAID	DIAMETER	STRENGTH	REUSABILITY	SALVAGE RATE	BEST FIT APPLICATION
<b>FN9 Series</b>	WRD - FN9	Semi-flat carrier braid	1.05 mm (Semi-flat)	515 lbs	Up to 12 cuts	Moderate	Apex line; high-torque shear on tough, aged adhesives.
<b>P10 Series</b>	WRD - P10	Thick solid braid	1.20 mm	468 lbs	Up to 12 cuts	Low	Commercial buses, trucks, and heavy machinery.
<b>P8 Series</b>	WRD - P8	Standard solid braid	1.00 mm	410 lbs	Up to 10 cuts	Moderate	General passenger sedans & light trucks (workhorse).
<b>X Series</b>	WRD - X	Slim solid braid	0.85 mm	371 lbs	Up to 7 cuts	Good	Optimal mid-gauge balance; preserves encapsulations.
<b>SF 301</b>	WRD - SF301	Flat braid	0.85 mm (Flat)	270 lbs	Up to 5 cuts	Good	Zero-clearance paths; slides between panels.
<b>P6 Series</b>	WRD - P6	Ultra-thin precision braid	0.65 mm	279 lbs	Up to 4 cuts	Great	Luxury European imports with zero-tolerance gaps.